

CARBON STEEL PIPE

IPS SEAMLESS PRESSURE TUBING

ASTM A-106 GRADES A & B, ASME SA-106 GRADES A & B

Pipe Size	O.D. (In.)	Schedule	Wall (In.)	I.D. (In.)	Wt./Ft. (lbs.)
Nominal					
1/8"	.405	40	.068	.269	.24
1/8"	.405	80	.095	.215	.31
Nominal					
1/4"	.540	40	.088	.364	.43
1/4"	.540	80	.119	.302	.54
Nominal					
3/8"	.675	40	.091	.493	.57
3/8"	.675	80	.126	.423	.74
Nominal					
1/2"	.840	40	.109	.622	.85
1/2"	.840	80	.147	.546	1.09
1/2"	.840	160	.188	.464	1.31
1/2"	.840	XXS	.294	.252	1.72
Nominal					
3/4"	1.050	40	.113	.824	1.13
3/4"	1.050	80	.154	.742	1.48
3/4"	1.050	160	.219	.612	1.95
3/4"	1.050	XXS	.308	.434	2.44

Pipe Size	O.D. (In.)	Schedule	Wall (In.)	I.D. (In.)	Wt./Ft. (lbs.)
Nominal					
1"	1.315	40	.133	1.049	1.68
1"	1.315	80	.179	.957	2.17
1"	1.315	160	.250	.815	2.85
1"	1.315	XXS	.358	.599	3.66
Nominal					
1-1/4"	1.660	40	.140	1.380	2.27
1-1/4"	1.660	80	.191	1.278	3.00
1-1/4"	1.660	160	.250	1.160	3.77
1-1/4"	1.660	XXS	.382	.896	5.22
Nominal					
1-1/2"	1.900	40	.145	1.610	2.72
1-1/2"	1.900	80	.200	1.500	3.63
1-1/2"	1.900	160	.281	1.338	4.86
1-1/2"	1.900	XXS	.400	1.100	6.41

CONTINUOUS WELD AND ELECTRIC RESISTANCE WELD STEEL PIPE

Marmon/Keystone stocks CW ASTM A-53 and ERW ASTM A-53 in Black and Galvanized available in both Plain End and Threaded & Coupled.

Pipe Size	O.D. (In.)	Schedule	Wall (In.)	I.D. (In.)	Wt./Ft. (lbs.)
Nominal					
1/8"	.405	40	.068	.269	.24
1/8"	.405	80	.095	.215	.31
Nominal					
1/4"	.540	40	.088	.364	.43
1/4"	.540	80	.119	.302	.54
Nominal					
3/8"	.675	40	.091	.493	.57
3/8"	.675	80	.126	.423	.74
Nominal					
1/2"	.840	40	.109	.622	.85
1/2"	.840	80	.147	.546	1.09
Nominal					
3/4"	1.050	40	.113	.824	1.13
3/4"	1.050	80	.154	.742	1.48
Nominal					
1"	1.315	40	.133	1.049	1.68
1"	1.315	80	.179	.957	2.17
Nominal					
1-1/4"	1.660	40	.140	1.380	2.27
1-1/4"	1.660	80	.191	1.278	3.00

Pipe Size	O.D. (In.)	Schedule	Wall (In.)	I.D. (In.)	Wt./Ft. (lbs.)
Nominal					
1-1/2"	1.900	40	.145	1.610	2.72
1-1/2"	1.900	80	.200	1.500	3.63
Nominal					
2"	2.375	40	.154	2.067	3.66
2"	2.375	80	.218	1.939	5.03
Nominal					
2-1/2"	2.875	40	.203	2.469	5.80
2-1/2"	2.875	80	.276	2.323	7.67
Nominal					
3"	3.500	40	.216	3.068	7.58
3"	3.500	80	.300	2.900	10.26
Nominal					
3-1/2"	4.000	40	.226	3.548	9.12
3-1/2"	4.000	80	.318	3.364	12.52
Nominal					
4"	4.500	40	.237	4.026	10.80
4"	4.500	80	.337	3.826	15.00

CARBON STEEL PIPE

SEAMLESS AND ELECTRIC RESISTANCE WELD STEEL PIPE

Marmon/Keystone stocks Seamless and Electric Resistance Weld
ASTM A-53/ASME SA-53 and Seamless ASTM A-106/ASME SA-106 and
Double Submerged Arc Weld API 5/L.

Pipe Size	O.D. (In.)	Schedule	Wall (In.)	I.D. (In.)	Desc./Grade	Wt./Ft. (lbs.)
Nominal						
2"	2.375	40	.154	2.067	ERW & SMLS	3.66
2"	2.375	80	.218	1.939	ERW & SMLS	5.03
2"	2.375	160	.344	1.687	SMLS	7.47
2"	2.375	XXS	.436	1.503	SMLS	9.04
Nominal						
2-1/2"	2.875	40	.203	2.469	ERW & SMLS	5.80
2-1/2"	2.875	80	.276	2.323	ERW & SMLS	7.67
2-1/2"	2.875	160	.375	2.125	SMLS	10.02
2-1/2"	2.875	XXS	.552	1.771	SMLS	13.71
Nominal						
3"	3.500	40	.216	3.068	ERW & SMLS	7.58
3"	3.500	80	.300	2.900	ERW & SMLS	10.26
3"	3.500	160	.438	2.624	SMLS	14.34
3"	3.500	XXS	.600	2.300	SMLS	18.60
Nominal						
3-1/2"	4.000	40	.226	3.548	ERW & SMLS	9.12
3-1/2"	4.000	80	.318	3.364	ERW & SMLS	12.52
3-1/2"	4.000	XXS	.636	2.728	SMLS	22.87
Nominal						
4"	4.500	40	.237	4.026	ERW & SMLS	10.80
4"	4.500	80	.337	3.826	ERW & SMLS	15.00
4"	4.500	120	.438	3.624	SMLS	19.02
4"	4.500	160	.531	3.438	SMLS	22.53
4"	4.500	XXS	.674	3.152	SMLS	27.57
Nominal						
5"	5.563	40	.258	5.047	ERW & SMLS	14.63
5"	5.563	80	.375	4.813	ERW & SMLS	20.80
5"	5.563	120	.500	4.563	SMLS	27.06
5"	5.563	160	.625	4.313	SMLS	32.99
5"	5.563	XXS	.750	4.063	SMLS	38.59
Nominal						
6"	6.625		.188	6.249	ERW	12.94
6"	6.625		.250	6.125	ERW	17.04
6"	6.625	40	.280	6.065	ERW & SMLS	18.99
6"	6.625	80	.432	5.761	ERW & SMLS	28.60
6"	6.625	120	.562	5.501	SMLS	36.43
6"	6.625	160	.719	5.187	SMLS	45.39
6"	6.625	XXS	.864	4.897	SMLS	53.21
Nominal						
7"	7.625	XS	.500	6.625	SMLS	38.08

Pipe Size	O.D. (In.)	Schedule	Wall (In.)	I.D. (In.)	Desc./Grade	Wt./Ft. (lbs.)
Nominal						
8"	8.625		.109	8.407	HREW	9.92
8"	8.625		.188	8.249	ERW	16.96
8"	8.625	20	.250	8.125	ERW	22.38
8"	8.625	30	.277	8.071	ERW	24.72
8"	8.625	40	.322	7.981	ERW & SMLS	28.58
8"	8.625	80	.500	7.625	ERW & SMLS	43.43
8"	8.625	100	.594	7.439	SMLS	51.00
8"	8.625	120	.719	7.189	SMLS	60.77
8"	8.625	XXS	.875	6.875	SMLS	72.49
8"	8.625	160	.906	6.813	SMLS	74.76
Nominal						
9"	9.625	40	.342	8.941	SMLS	33.90
Nominal						
10"	10.750		.188	10.374	ERW	21.23
10"	10.750	20	.250	10.250	ERW & SMLS	28.06
10"	10.750	30	.307	10.136	ERW	34.27
10"	10.750	40	.365	10.020	ERW & SMLS	40.52
10"	10.750	XS	.500	9.750	ERW & SMLS	54.79
10"	10.750	80	.594	9.562	SMLS	64.49
10"	10.750	100	.719	9.312	SMLS	77.10
10"	10.750	120	.844	9.062	SMLS	89.38
10"	10.750	140	1.000	8.750	SMLS	104.23
10"	10.750	160	1.125	8.500	SMLS	115.75
10"	10.750		1.250	8.250	SMLS	126.94
10"	10.750		1.500	7.750	SMLS	148.32
10"	10.750		1.750	7.250	SMLS	168.21
10"	10.750		2.000	6.750	SMLS	186.90
10"	10.750		2.500	5.750	SMLS	220.28
Nominal						
11"	11.750	Std.	.375	11.000	SMLS	45.60
11"	11.750	XXS	.844	10.062	SMLS	98.40
11"	11.750		1.000	9.750	SMLS	114.92
11"	11.750		1.250	9.250	SMLS	140.31
Nominal						
12"	12.750		.188	12.374	ERW	25.25
12"	12.750	20	.250	12.250	ERW	33.41
12"	12.750	Std.	.375	12.000	ERW & SMLS	49.61
12"	12.750	40	.406	11.938	ERW & SMLS	53.57
12"	12.750	XS	.500	11.750	ERW & SMLS	65.48
12"	12.750	60	.562	11.626	SMLS	73.22
12"	12.750	80	.688	11.374	SMLS	88.71
12"	12.750	100	.844	11.062	SMLS	107.42
12"	12.750	120	1.000	10.750	SMLS	125.61
12"	12.750	140	1.125	10.500	SMLS	139.81
12"	12.750	160	1.312	10.126	SMLS	160.42
12"	12.750		2.000	8.750	SMLS	229.84



CARBON STEEL PIPE

SEAMLESS AND ELECTRIC RESISTANCE WELD STEEL PIPE

Marmon/Keystone stocks Seamless and Electric Resistance Weld
 ASTM A-53/ASME SA-53 and Seamless ASTM A-106/ASME SA-106
 and Double Submerged Arc Weld API 5/L.
 Hot Rolled Electric Welded ASTM A-134 or ASTM A-135

Pipe Size	O.D. (In.)	Schedule	Wall (In.)	I.D. (In.)	Desc./Grade	Wt./Ft. (lbs.)
13" O.D.						
13"	13.000		.500	12.000	SMLS	66.81
13"	13.000		.750	11.500	SMLS	98.21
13"	13.000		1.000	11.000	SMLS	128.28
13"	13.000		1.250	10.500	SMLS	157.01
13"	13.000		1.500	10.000	SMLS	184.40
13"	13.000		1.750	9.500	SMLS	210.46
13"	13.000		2.000	9.000	SMLS	235.18
13"	13.000		2.500	8.000	SMLS	280.61
13"	13.000		3.000	7.000	SMLS	320.70

13-3/8" O.D.						
13-3/8"	13.375		.500	12.375	SMLS	68.82
13-3/8"	13.375		.750	11.875	SMLS	101.22
13-3/8"	13.375		1.000	11.375	SMLS	132.29
13-3/8"	13.375		1.250	10.875	SMLS	162.02
13-3/8"	13.375		1.500	10.375	SMLS	190.42
13-3/8"	13.375		2.000	9.375	SMLS	243.20

14" O.D.						
14"	14.000	10	.250	13.500	ERW	36.75
14"	14.000	20	.312	13.376	ERW	45.65
14"	14.000	Std.	.375	13.250	ERW & SMLS	54.62
14"	14.000	40	.438	13.124	SMLS	63.50
14"	14.000	XS	.500	13.000	ERW & SMLS	72.16
14"	14.000	60	.594	12.812	SMLS	85.13
14"	14.000	80	.750	12.500	SMLS	106.23
14"	14.000	100	.938	12.124	SMLS	130.98
14"	14.000	120	1.094	11.812	SMLS	150.93
14"	14.000	140	1.250	11.500	SMLS	170.37
14"	14.000	160	1.406	11.188	SMLS	189.29
14"	14.000		1.500	11.000	SMLS	200.44
14"	14.000		1.750	10.500	SMLS	229.17
14"	14.000		2.000	10.000	SMLS	256.56
14"	14.000		2.250	9.500	SMLS	282.62
14"	14.000		2.500	9.000	SMLS	307.34
14"	14.000		3.000	8.000	SMLS	352.77

14-3/8" O.D.						
14-3/8"	14.375		.500	13.375	SMLS	74.16
14-3/8"	14.375		.750	12.875	SMLS	109.24
14-3/8"	14.375		1.000	12.375	SMLS	142.98
14-3/8"	14.375		1.250	11.875	SMLS	175.38
14-3/8"	14.375		1.500	11.375	SMLS	206.45
14-3/8"	14.375		2.000	10.375	SMLS	264.58
14-3/8"	14.375		2.500	9.375	SMLS	317.36

15" O.D.						
15"	15.000		.375	14.250	SMLS	58.63
15"	15.000		.500	14.000	SMLS	77.50
15"	15.000		.750	13.500	SMLS	114.25
15"	15.000		1.000	13.000	SMLS	149.66
15"	15.000		1.250	12.500	SMLS	183.73
15"	15.000		1.500	12.000	SMLS	216.47
15"	15.000		1.750	11.500	SMLS	247.87
15"	15.000		2.000	11.000	SMLS	277.94
15"	15.000		2.500	10.000	SMLS	334.06
15"	15.000		2.875	9.250	SMLS	372.65

Pipe Size	O.D. (In.)	Schedule	Wall (In.)	I.D. (In.)	Desc./Grade	Wt./Ft. (lbs.)
15-1/2" O.D.						
15-1/2"	15.500		.500	14.500	SMLS	80.18
15-1/2"	15.500		.750	14.000	SMLS	118.26
15-1/2"	15.500		1.000	13.500	SMLS	155.01
15-1/2"	15.500		1.250	13.000	SMLS	190.42
15-1/2"	15.500		1.500	12.500	SMLS	224.49
15-1/2"	15.500		1.750	12.000	SMLS	257.23
15-1/2"	15.500		2.000	11.500	SMLS	288.63
15-1/2"	15.500		2.500	10.500	SMLS	347.43

16" O.D.						
16"	16.000		.188	15.624	ERW	31.78
16"	16.000	10	.250	15.500	ERW	42.09
16"	16.000	Std.	.375	15.250	ERW & SMLS	62.64
16"	16.000	XS	.500	15.000	ERW & SMLS	82.85
16"	16.000	60	.656	14.688	SMLS	107.60
16"	16.000	80	.844	14.312	SMLS	136.74
16"	16.000	100	1.031	13.938	SMLS	164.98
16"	16.000	120	1.219	13.562	SMLS	192.61
16"	16.000	160	1.594	12.812	SMLS	245.48
16"	16.000		2.000	12.000	SMLS	299.32
16"	16.000		2.250	11.500	SMLS	330.72
16"	16.000		2.500	11.000	SMLS	360.79
16"	16.000		3.000	10.000	SMLS	416.91

16-1/2" O.D.						
16-1/2"	16.500		.500	15.500	SMLS	85.52
16-1/2"	16.500		.750	15.000	SMLS	126.28
16-1/2"	16.500		1.000	14.500	SMLS	165.70
16-1/2"	16.500		1.250	14.000	SMLS	203.78
16-1/2"	16.500		1.500	13.500	SMLS	240.53
16-1/2"	16.500		2.000	12.500	SMLS	310.01

17" O.D.						
17"	17.000		.500	16.000	SMLS	88.19
17"	17.000		.750	15.500	SMLS	130.28
17"	17.000		1.000	15.000	SMLS	171.04
17"	17.000		1.250	14.500	SMLS	210.46
17"	17.000		1.500	14.000	SMLS	248.54
17"	17.000		1.750	13.500	SMLS	285.29
17"	17.000		2.000	13.000	SMLS	320.70
17"	17.000		2.500	12.000	SMLS	387.51
17"	17.000		2.875	11.250	SMLS	434.11

17-1/2" O.D.						
17-1/2"	17.500		.750	16.000	SMLS	134.29
17-1/2"	17.500		1.000	15.500	SMLS	176.39
17-1/2"	17.500		1.250	15.000	SMLS	217.14
17-1/2"	17.500		1.500	14.500	SMLS	256.56
17-1/2"	17.500		2.000	13.500	SMLS	331.39

17-3/4" O.D.						
17-3/4"	17.750		2.875	12.000	SMLS	457.16

CARBON STEEL PIPE

SEAMLESS AND ELECTRIC RESISTANCE WELD STEEL PIPE

Marmon/Keystone stocks Seamless and Electric Resistance Weld
ASTM A-53/ASME SA-53 and Seamless ASTM A-106/ASME SA-106
and Double Submerged Arc Weld API 5/L.

Pipe Size	O.D. (In.)	Schedule	Wall (In.)	I.D. (In.)	Desc./Grade	Wt./Ft. (lbs.)
18" O.D.						
18"	18.000	10	.250	17.500	ERW	47.44
18"	18.000	Std.	.375	17.250	ERW & SMLS	70.65
18"	18.000	XS	.500	17.000	ERW & SMLS	93.54
18"	18.000	40	.562	16.876	SMLS	104.76
18"	18.000	60	.750	16.500	SMLS	138.30
18"	18.000	80	.938	16.124	SMLS	171.08
18"	18.000	100	1.156	15.688	SMLS	208.15
18"	18.000	140	1.562	14.876	SMLS	274.48
18"	18.000	160	1.781	14.438	SMLS	308.79
18"	18.000		2.000	14.000	SMLS	342.08
18"	18.000		2.500	13.000	SMLS	414.24
18"	18.000		3.000	12.000	SMLS	481.05
18-1/2" O.D.						
18-1/2"	18.500		.750	17.000	SMLS	142.31
18-1/2"	18.500		1.000	16.500	SMLS	187.08
18-1/2"	18.500		1.250	16.000	SMLS	230.50
18-1/2"	18.500		1.500	15.500	SMLS	272.60
18-1/2"	18.500		2.000	14.500	SMLS	352.77
19" O.D.						
19"	19.000		.500	18.000	SMLS	98.88
19"	19.000		.750	17.500	SMLS	146.32
19"	19.000		1.000	17.000	SMLS	192.42
19"	19.000		1.250	16.500	SMLS	237.18
19"	19.000		1.500	16.000	SMLS	280.61
19"	19.000		1.750	15.500	SMLS	322.70
19"	19.000		2.000	15.000	SMLS	363.46
19"	19.000		2.500	14.000	SMLS	440.96
19"	19.000		3.000	13.000	SMLS	513.12
20" O.D.						
20"	20.000	10	.250	19.500	ERW	52.78
20"	20.000	Std.	.375	19.250	ERW & SMLS	78.67
20"	20.000	XS	.500	19.000	ERW & SMLS	104.23
20"	20.000	40	.594	18.812	SMLS	123.23
20"	20.000	60	.812	18.376	SMLS	166.56
20"	20.000	80	1.031	17.938	SMLS	209.06
20"	20.000	100	1.281	17.438	SMLS	256.34
20"	20.000	120	1.500	17.000	SMLS	296.65
20"	20.000	140	1.750	16.500	SMLS	341.41
20"	20.000	160	1.969	16.064	SMLS	379.53
20"	20.000		2.500	15.000	SMLS	467.69
20"	20.000		3.000	14.000	SMLS	545.19
21" O.D.						
21"	21.000		.750	19.500	SMLS	162.35
21"	21.000		1.000	19.000	SMLS	213.80
21"	21.000		1.500	18.000	SMLS	312.68
21"	21.000		1.750	17.500	SMLS	360.12
21"	21.000		2.000	17.000	SMLS	406.22
21"	21.000		2.500	16.000	SMLS	494.41
21"	21.000		3.000	15.000	SMLS	577.26

Pipe Size	O.D. (In.)	Schedule	Wall (In.)	I.D. (In.)	Desc./Grade	Wt./Ft.
22" O.D.						
22"	22.000	10	.250	21.500	ERW	58.13
22"	22.000	Std.	.375	21.250	ERW & SMLS	86.69
22"	22.000	XS	.500	21.000	ERW & SMLS	114.92
22"	22.000		.750	20.500	SMLS	170.37
22"	22.000		1.000	20.000	SMLS	224.49
22"	22.000		1.500	19.000	SMLS	328.72
22"	22.000		2.000	18.000	SMLS	427.60
22"	22.000		2.500	17.000	SMLS	521.14
22"	22.000		3.000	16.000	SMLS	609.33
23" O.D.						
23"	23.000		.500	22.000	SMLS	120.26
23"	23.000		.750	21.500	SMLS	178.39
23"	23.000		1.000	21.000	SMLS	235.18
23"	23.000		1.500	20.000	SMLS	344.75
23"	23.000		2.000	19.000	SMLS	448.98
23"	23.000		2.500	18.000	SMLS	547.86
23"	23.000		3.000	17.000	SMLS	641.40
24" O.D.						
24"	24.000	10	.250	23.500	ERW	63.47
24"	24.000		.312	23.376	ERW	79.01
24"	24.000	Std.	.375	23.250	ERW & SMLS	94.71
24"	24.000	XS	.500	23.000	ERW & SMLS	125.61
24"	24.000	40	.688	22.624	SMLS	171.45
24"	24.000	60	.969	22.064	SMLS	238.57
24"	24.000	80	1.219	21.562	SMLS	296.86
24"	24.000	100	1.531	20.938	SMLS	367.74
24"	24.000	120	1.812	20.376	SMLS	429.79
24"	24.000		2.500	19.000	SMLS	574.59
24"	24.000		3.000	18.000	SMLS	673.47
26" O.D.						
26"	26.000	XS	.500	25.000	ERW	136.30
26"	26.000		1.500	23.000	SMLS	392.86
26"	26.000		2.000	22.000	SMLS	513.12
26"	26.000		3.000	20.000	SMLS	737.61
30" O.D.						
30"	30.000	Std.	.375	29.250	DSAW	118.76
30"	30.000	XS	.500	29.000	DSAW	157.68
36" O.D.						
36"	36.000	Std.	.375	35.250	DSAW	142.81
36"	36.000	XS	.500	35.000	DSAW	189.75
48" O.D.						
48"	48.000	Std.	.375	47.250	DSAW	190.92
48"	48.000	XS	.500	47.000	DSAW	253.89



CARBON MECHANICAL TUBING

CDS - COLD DRAWN SEAMLESS, ASTM 519
DOM - DRAWN OVER MANDREL, ASTM 513
HREW - HOT ROLLED ELECTRIC WELD, ASTM 513
CREW - COLD ROLLED ELECTRIC WELD, ASTM 513
CDBW - COLD DRAWN BUTT WELD, ASTM 512

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
1/8" O.D.				
.125	.049	.027	DOM	.040
3/16" O.D.				
.188	.065	.058	DOM	.090
1/4" O.D.				
.250	.028	.194	DOM	.066
.250	.035	.180	DOM	.080
.250	.049	.152	DOM	.105
5/16" O.D.				
.313	.028	.257	DOM	.085
.313	.035	.243	DOM	.104
.313	.049	.215	DOM	.138
3/8" O.D.				
.375	.028	.319	DOM	.104
.375	.035	.305	DOM	.127
.375	.049	.277	CREW	.171
.375	.049	.277	DOM	.171
.375	.058	.259	DOM	.196
.375	.065	.245	DOM	.215
.375	.083	.209	DOM	.259
.375	.095	.185	CDS	.284
.375	.120	.135	CDS	.327
7/16" O.D.				
.438	.049	.340	DOM	.204
.438	.065	.308	DOM	.259
.438*	.120	.198	DOM	.408
1/2" O.D.				
.500	.035	.430	DOM	.174
.500	.049	.402	DOM	.236
.500	.049	.402	CREW	.236
.500	.058	.384	DOM	.274
.500	.065	.370	DOM	.302
.500	.065	.370	CREW	.302
.500	.065	.370	HREW	.302
.500	.083	.334	DOM	.370
.500	.095	.310	DOM	.411
.500	.109	.282	DOM	.455
.500	.120	.260	DOM	.487
.500	.125	.250	DOM	.500
.500	.156	.188	CDS	.573

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
9/16" O.D.				
.563	.022	.519	DOM	.127
.563	.065	.433	DOM	.346
.563	.083	.397	DOM	.426
.563	.095	.373	DOM	.475
.563	.109	.345	CDS	.529
.563	.120	.323	DOM	.568
5/8" O.D.				
.625	.049	.527	DOM	.301
.625	.049	.527	CREW	.301
.625	.058	.509	DOM	.351
.625	.065	.495	DOM	.389
.625	.065	.495	CREW	.389
.625	.065	.495	HREW	.389
.625	.083	.459	DOM	.481
.625	.083	.459	HREW	.481
.625	.093	.439	DOM	.530
.625	.095	.435	DOM	.538
.625	.095	.435	CDBW	.538
.625	.109	.407	DOM	.601
.625	.120	.385	DOM	.647
.625	.125	.375	DOM	.670
.625	.134	.357	DOM	.703
.625	.156	.313	DOM	.781
.625*	.188	.250	DOM	.877
11/16" O.D.				
.688	.065	.558	DOM	.433
.688	.083	.522	DOM	.536
.688	.095	.498	DOM	.602
.688	.120	.448	DOM	.728
.742" O.D.				
.742	.114	.514	DOM	.765

*Purchased O.D. & Wall

CDS - COLD DRAWN SEAMLESS, ASTM 519
DOM - DRAWN OVER MANDREL, ASTM 513
HREW - HOT ROLLED ELECTRIC WELD, ASTM 513
CDBW - COLD DRAWN BUTT WELD, ASTM 512

CARBON MECHANICAL TUBING

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
3/4" O.D.				
.750	.033	.684	DOM	.253
.750	.035	.680	DOM	.267
.750	.049	.652	DOM	.367
.750	.049	.652	CREW	.367
.750	.060	.630	DOM	.442
.750	.065	.620	DOM	.476
.750	.065	.620	CREW	.476
.750	.065	.620	HREW	.476
.750	.083	.584	DOM	.591
.750	.083	.584	HREW	.591
.750	.090	.570	DOM	.634
.750	.095	.560	DOM	.665
.750	.095	.560	HREW	.665
.750	.109	.532	DOM	.746
.750	.120	.510	DOM	.807
.750	.120	.510	HREW	.807
.750	.125	.500	DOM	.834
.750	.134	.482	DOM	.882
.750	.138	.474	DOM	.900
.750	.156	.438	DOM	.990
.750	.156	.438	CDBW	.990
.750	.169	.412	DOM	1.051
.750	.172	.406	CDBW	1.062
.750	.188	.375	DOM	1.128
.750**	.219	.312	DOM	1.242
.750**	.250	.250	DOM	1.335
13/16" O.D.				
.813	.065	.638	DOM	.519
.813	.069	.675	DOM	.548
.813	.083	.647	DOM	.647
.813	.120	.573	DOM	.888
.813	.120	.573	CDBW	.985
.813	.134	.545	DOM	.972
.840" O.D.				
.840	.109	.622	HREW HY	.850
7/8" O.D.				
.875	.049	.777	DOM	.432
.875	.049	.777	CREW	.432
.875	.058	.759	DOM	.506
.875	.060	.755	DOM	.522
.875	.065	.745	DOM	.562
.875	.065	.745	CREW	.562
.875	.065	.745	HREW	.562
.875	.083	.709	DOM	.702
.875	.083	.709	HREW	.702
.875	.095	.685	DOM	.791
.875	.095	.685	HREW	.791
.875	.109	.657	DOM	.892
.875	.120	.635	DOM	.968
.875	.156	.563	DOM	1.198
.875	.188	.500	DOM	1.379
.875	.219	.437	DOM	1.534
.875*	.250	.375	DOM	1.669

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
15/16" O.D.				
.938	.120	.698	DOM	1.048
.938	.134	.670	DOM	1.151
.938	.188	.562	DOM	1.506
1" O.D.				
1.000	.049	.902	DOM	.498
1.000	.049	.902	CREW	.498
1.000	.065	.870	DOM	.649
1.000	.065	.870	CREW	.649
1.000	.065	.870	HREW	.649
1.000	.083	.834	DOM	.813
1.000	.083	.834	HREW	.813
1.000	.095	.810	DOM	.918
1.000	.095	.810	HREW	.918
1.000	.109	.782	DOM	1.037
1.000	.109	.782	HREW	1.037
1.000	.120	.760	DOM	1.128
1.000	.120	.760	CDBW	1.128
1.000	.120	.760	HREW	1.128
1.000	.134	.732	DOM	1.239
1.000	.156	.688	DOM	1.406
1.000	.172	.656	CDBW	1.517
1.000	.180	.640	CDBW	1.576
1.000	.188	.625	DOM	1.630
1.000	.219	.562	DOM	1.827
1.000	.250	.500	DOM	2.003
1.000	.281	.438	DOM	2.158
1.000**	.313	.375	DOM	2.297
1.000*	.375	.250	CDS	2.503
1.050" O.D.				
1.050	.113	.824	HREW HY	1.130
1-1/16" O.D.				
1.063	.083	.897	DOM	.869
1.063	.095	.873	DOM	.982
1.063	.120	.823	DOM	1.209
1.063	.188	.687	DOM	1.757
1.063	.250	.563	DOM	2.171

*Purchased O.D. & Wall

**Purchased O.D. & Wall with A-519 wall tolerances.

CARBON MECHANICAL TUBING

CREW – COLD ROLLED ELECTRIC WELD, ASTM 513
HRS – HOT ROLLED SEAMLESS, ASTM 519
HY – HIGH YIELD WELDED

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
1-1/8" O.D.				
1.125	.065	.995	DOM	.736
1.125	.083	.959	HREW	.924
1.125	.095	.935	DOM	1.045
1.125	.109	.907	DOM	1.183
1.125	.120	.885	DOM	1.288
1.125	.125	.875	DOM	1.340
1.125	.156	.813	DOM	1.614
1.125	.180	.765	CDBWST	1.817
1.125	.188	.750	DOM	1.881
1.125	.219	.688	DOM	2.119
1.125	.250	.625	DOM	2.336
1.125	.281	.563	DOM	2.533
1.125	.313	.500	DOM	2.714
1-3/16" O.D.				
1.188	.083	1.022	DOM	.979
1.188	.156	.876	DOM	1.719
1.188	.188	.813	DOM	2.008
1-1/4" O.D.				
1.250	.049	1.152	CREW	.629
1.250	.058	1.134	DOM	.751
1.250	.065	1.120	DOM	.823
1.250	.065	1.120	CREW	.823
1.250	.065	1.120	HREW	.823
1.250	.083	1.084	DOM	1.034
1.250	.083	1.084	HREW	1.034
1.250	.095	1.060	DOM	1.172
1.250	.095	1.060	HREW	1.172
1.250	.109	1.032	DOM	1.328
1.250	.120	1.010	DOM	1.448
1.250	.120	1.010	HREW	1.448
1.250	.125	1.000	DOM	1.510
1.250	.134	.982	DOM	1.597
1.250	.156	.938	DOM	1.823
1.250	.188	.875	DOM	2.132
1.250	.219	.813	DOM	2.411
1.250	.235	.780	CDBW	2.547
1.250	.250	.750	DOM	2.670
1.250	.281	.688	DOM	2.908
1.250	.313	.625	DOM	3.132
1.250	.344	.562	DOM	3.329
1.250**	.375	.500	DOM	3.504
1.250*	.438	.375	CDS	3.798

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
1-5/16" O.D.				
1.313	.065	1.183	DOM	.865
1.313	.120	1.072	DOM	1.529
1.313	.134	1.045	DOM	1.687
1.313	.156	1.000	DOM	1.928
1.313	.188	.937	DOM	2.259
1.313	.219	.875	DOM	2.559
1.313	.250	.813	DOM	2.838
1.313**	.375	.563	DOM	3.757
1.315" O.D.				
1.315	.109	1.097	HREW HY	1.400
1.315	.133	1.049	HREW HY	1.680
1-3/8" O.D.				
1.375	.049	1.277	DOM	.694
1.375	.049	1.277	CREW	.694
1.375	.065	1.245	DOM	.909
1.375	.065	1.245	CREW	.909
1.375	.083	1.209	HREW	1.145
1.375	.095	1.185	DOM	1.299
1.375	.120	1.135	DOM	1.608
1.375	.120	1.135	HREW	1.608
1.375	.125	1.125	DOM	1.660
1.375	.156	1.063	DOM	2.031
1.375	.172	1.031	CDBW	2.210
1.375	.180	1.015	DOM	2.297
1.375	.188	1.000	DOM	2.383
1.375	.219	.938	DOM	2.704
1.375	.250	.875	DOM	3.004
1.375	.281	.813	DOM	3.283
1.375	.313	.750	DOM	3.550
1.375**	.375	.625	DOM	4.005
1-7/16" O.D.				
1.438	.156	1.125	DOM	2.136
1.438	.188	1.062	DOM	2.510
1.438	.250	.938	DOM	3.172

*Purchased O.D. & Wall

**Purchased O.D. & Wall with A-519 wall tolerances.

CDS - COLD DRAWN SEAMLESS, ASTM 519
DOM - DRAWN OVER MANDREL, ASTM 513
HREW - HOT ROLLED ELECTRIC WELD, ASTM 513
CDBW - COLD DRAWN BUTT WELD, ASTM 512

CARBON MECHANICAL TUBING

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
1-1/2" O.D.				
1.500	.049	1.402	CREW	.759
1.500	.065	1.370	DOM	.996
1.500	.065	1.370	CREW	.996
1.500	.065	1.370	HREW	.996
1.500	.083	1.334	DOM	1.256
1.500	.083	1.334	CREW	1.256
1.500	.083	1.334	HREW	1.256
1.500	.095	1.310	DOM	1.426
1.500	.095	1.310	HREW	1.426
1.500	.109	1.282	DOM	1.619
1.500	.120	1.260	DOM	1.769
1.500	.120	1.260	HREW	1.769
1.500	.134	1.232	DOM	1.955
1.500	.156	1.188	CDBW	2.239
1.500	.156	1.188	DOM	2.239
1.500	.188	1.125	DOM	2.634
1.500	.219	1.062	DOM	2.996
1.500	.234	1.032	DOM	3.160
1.500	.240	1.020	CDBW	3.230
1.500	.248	1.004	CDBW	3.320
1.500	.250	1.000	DOM	3.338
1.500	.281	.938	DOM	3.658
1.500	.313	.875	DOM	3.968
1.500	.344	.812	DOM	4.247
1.500	.375	.750	DOM/CDS	4.506
1.500*	.438	.625	CDS	4.968
1.500*	.500	.500	CDS	5.340
1-9/16" O.D.				
1.563	.120	1.323	DOM	1.849
1.563	.156	1.250	DOM	2.344
1.563	.250	1.063	DOM	3.506
1.563	.250	1.063	CDBW	3.506
1-5/8" O.D.				
1.625	.049	1.527	CREW	.825
1.625	.065	1.495	DOM	1.083
1.625	.065	1.495	CREW	1.083
1.625	.095	1.435	HREW	1.552
1.625	.095	1.435	DOM	1.552
1.625	.120	1.385	HREW	1.929
1.625	.120	1.385	DOM	1.929
1.625	.134	1.357	HREW	2.130
1.625	.156	1.313	DOM	2.447
1.625	.172	1.281	DOM	2.669
1.625	.180	1.265	DOM	2.778

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
1-5/8" O.D. (continued)				
1.625	.188	1.250	DOM	2.885
1.625	.219	1.187	DOM	3.289
1.625	.250	1.125	DOM	3.671
1.625	.281	1.063	DOM	4.033
1.625	.313	.999	DOM	4.386
1.625	.375	.875	DOM	5.006
1.625*	.438	.749	CDS	5.553
1.625*	.500	.625	CDS	6.008
1.660" O.D.				
1.660	.120	1.420	HREW HY	1.980
1.660	.140	1.380	HREW HY	2.270
1-11/16" O.D.				
1.688	.188	1.312	DOM	3.012
1.688	.250	1.188	DOM	3.839
1-3/4" O.D.				
1.750	.049	1.652	CREW	.890
1.750	.065	1.620	CREW	1.170
1.750	.065	1.620	DOM	1.170
1.750	.065	1.620	HREW	1.170
1.750	.083	1.584	DOM	1.478
1.750	.083	1.584	HREW	1.478
1.750	.095	1.560	DOM	1.679
1.750	.095	1.560	HREW	1.679
1.750	.109	1.532	DOM	1.910
1.750	.120	1.510	HREW	2.089
1.750	.120	1.510	DOM	2.089
1.750	.134	1.482	DOM	2.313
1.750	.134	1.482	HREW	2.312
1.750	.156	1.438	DOM	2.656
1.750	.188	1.375	DOM	3.136
1.750	.219	1.312	DOM	3.581
1.750	.235	1.280	DOM	3.802
1.750	.250	1.250	DOM	4.005
1.750	.281	1.188	DOM	4.409
1.750	.313	1.124	DOM	4.804
1.750	.359	1.032	DOM	5.333
1.750	.375	1.000	DOM	5.507
1.750*	.438	.875	CDS	6.137
1.750*	.500	.750	CDS	6.675

* Purchased O.D. & Wall

8

CARBON MECHANICAL TUBING

CREW – COLD ROLLED ELECTRIC WELD, ASTM 513
HRS – HOT ROLLED SEAMLESS, ASTM 519
HY – HIGH YIELD WELDED

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
1-7/8" O.D.				
1.875	.065	1.745	HREW	1.257
1.875	.095	1.685	DOM	1.806
1.875	.120	1.635	DOM	2.249
1.875	.156	1.563	DOM	2.864
1.875	.188	1.500	DOM	3.387
1.875	.219	1.438	DOM	3.873
1.875	.250	1.375	DOM	4.339
1.875	.281	1.313	DOM	4.784
1.875	.313	1.250	DOM	5.222
1.875	.375	1.125	DOM	6.008
1.875	.438	1.000	CDS	6.722
1.875*	.500	.875	CDS	7.343
1.900" O.D.				
1.900	.109	1.682	HREW HY	2.080
1.900	.145	1.610	HREW HY	2.720
2" O.D.				
2.000	.049	1.902	CREW	1.021
2.000	.065	1.870	CREW	1.343
2.000	.065	1.870	HREW	1.343
2.000	.065	1.870	DOM	1.343
2.000	.083	1.834	HREW	1.699
2.000	.083	1.834	DOM	1.699
2.000	.095	1.810	HREW	1.933
2.000	.095	1.810	DOM	1.933
2.000	.109	1.782	DOM	2.201
2.000	.120	1.760	HREW	2.409
2.000	.120	1.760	DOM	2.409
2.000	.125	1.750	DOM	2.503
2.000	.134	1.732	DOM	2.670
2.000	.156	1.688	DOM	3.072
2.000	.188	1.624	DOM	3.638
2.000	.219	1.562	DOM	4.166
2.000	.240	1.520	CDBW	4.511
2.000	.245	1.510	DOM	4.562
2.000	.250	1.500	DOM	4.673
2.000	.250	1.500	CDBW	4.673
2.000	.281	1.438	DOM	5.159
2.000	.313	1.375	DOM	5.639
2.000	.344	1.312	DOM	6.084
2.000	.368	1.264	DOM	6.414

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
2" O.D. (continued)				
2.000	.375	1.250	DOM	6.508
2.000	.438	1.125	DOM	7.307
2.000	.485	1.030	CDS	7.847
2.000	.500	1.000	DOM/CDS	8.010
2.000*	.563	.874	CDS	8.640
2.000*	.625	.750	CDS	9.178
2.000*	.750	.500	CDS	10.010
2.055" O.D.				
2.055	.270	1.515	CDBW	5.147
2-1/8" O.D.				
2.125	.049	2.027	CREW	1.086
2.125	.049	2.027	DOM	1.090
2.125	.065	1.995	CREW	1.430
2.125	.065	1.995	DOM	1.430
2.125	.120	1.885	DOM	2.570
2.125	.120	1.885	HREW	2.570
2.125	.188	1.750	DOM	3.889
2.125	.219	1.687	DOM	4.458
2.125	.250	1.625	DOM	5.006
2.125	.281	1.563	DOM	5.534
2.125	.313	1.500	DOM	6.057
2.125	.375	1.375	DOM	7.009
2.125	.438	1.250	DOM	7.892
2.125	.500	1.125	DOM	8.678
2.125*	.563	1.000	CDS	9.392
2-3/16" O.D.				
2.188	.313	1.562	DOM	6.268

*Purchased O.D. & Wall

CDS - COLD DRAWN SEAMLESS, ASTM 519
DOM - DRAWN OVER MANDREL, ASTM 513
HREW - HOT ROLLED ELECTRIC WELD, ASTM 513
CDBW - COLD DRAWN BUTT WELD, ASTM 512

CARBON MECHANICAL TUBING

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
---------------	---------------	---------------	---------------------	-------------------

2-1/4" O.D.

2.250	.065	2.120	CREW	1.517
2.250	.065	2.120	DOM	1.517
2.250	.083	2.084	HREW	1.921
2.250	.083	2.084	DOM	1.921
2.250	.095	2.060	DOM	2.186
2.250	.120	2.010	DOM	2.730
2.250	.125	2.000	DOM	2.837
2.250	.156	1.938	DOM	3.489
2.250	.188	1.875	DOM	4.140
2.250	.219	1.812	DOM	4.750
2.250	.250	1.750	DOM	5.340
2.250	.281	1.688	DOM	5.909
2.250	.313	1.625	DOM	6.475
2.250	.313	1.625	CDBW	6.475
2.250	.344	1.563	DOM	7.002
2.250	.375	1.500	DOM	7.509
2.250	.438	1.375	DOM/CDS	8.476
2.250	.500	1.250	CDS	9.345
2.250*	.563	1.124	CDS	10.140
2.250*	.625	1.000	CDS	10.850
2.250*	.750	.750	CDS	12.020

2-3/8" O.D.

2.375	.065	2.245	CREW	1.604
2.375	.109	2.157	HREW HY	2.638
2.375	.120	2.135	HREW	2.890
2.375	.120	2.135	DOM	2.890
2.375	.154	2.067	HREW HY	3.650
2.375	.156	2.063	DOM	3.697
2.375	.188	2.000	DOM	4.391
2.375	.219	1.937	DOM	5.043
2.375	.250	1.875	DOM	5.674
2.375	.281	1.813	DOM	6.284
2.375	.313	1.750	DOM	6.893
2.375	.375	1.625	DOM	8.010
2.375	.438	1.500	DOM	9.061
2.375	.500	1.375	DOM	10.010
2.375	.563	1.249	CDS	10.900
2.375*	.625	1.125	CDS	11.680

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
---------------	---------------	---------------	---------------------	-------------------

2-1/2" O.D.

2.500	.049	2.402	CREW	1.280
2.500	.065	2.370	CREW	1.690
2.500	.065	2.370	HREW	1.690
2.500	.065	2.370	DOM	1.690
2.500	.083	2.334	HREW	2.143
2.500	.083	2.334	DOM	2.143
2.500	.095	2.310	DOM	2.440
2.500	.109	2.282	DOM	2.783
2.500	.120	2.260	HREW	3.050
2.500	.120	2.260	DOM	3.050
2.500	.156	2.188	DOM	3.905
2.500	.188	2.125	DOM	4.642
2.500	.219	2.062	DOM	5.335
2.500	.250	2.000	DOM	6.008
2.500	.313	1.875	DOM	7.311
2.500	.344	1.813	DOM	7.921
2.500	.375	1.750	DOM	8.511
2.500	.438	1.625	DOM	9.646
2.500	.483	1.530	DOM	10.220
2.500	.493	1.514	DOM	10.570
2.500	.500	1.500	DOM	10.680
2.500	.563	1.375	DOM/CDS	11.650
2.500	.625	1.250	DOM	12.520
2.500*	.750	1.000	CDS	14.020

*Purchased O.D. & Wall



CARBON MECHANICAL TUBING

CREW – COLD ROLLED ELECTRIC WELD, ASTM 513
HRS – HOT ROLLED SEAMLESS, ASTM 519
HY – HIGH YIELD WELDED

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
---------------	---------------	---------------	---------------------	-------------------

2-5/8" O.D.

2.625	.120	2.385	DOM	3.210
2.625	.156	2.312	DOM	4.114
2.625	.188	2.250	DOM	4.893
2.625	.250	2.125	DOM	6.341
2.625	.281	2.063	DOM	7.035
2.625	.313	2.000	DOM	7.729
2.625	.375	1.875	DOM	9.011
2.625	.438	1.750	DOM	10.230
2.625	.500	1.625	DOM	11.350
2.625	.563	1.499	DOM	12.398
2.625	.625	1.375	DOM	13.350

2-3/4" O.D.

2.750	.065	2.620	CREW	1.864
2.750	.065	2.620	DOM	1.864
2.750	.083	2.584	DOM	2.364
2.750	.120	2.510	HREW	3.371
2.750	.120	2.510	DOM	3.371
2.750	.125	2.500	DOM	3.504
2.750	.188	2.375	DOM	5.144
2.750	.219	2.312	DOM	5.920
2.750	.250	2.250	DOM	6.675
2.750	.281	2.188	DOM	7.410
2.750	.313	2.125	DOM	8.147
2.750	.344	2.062	DOM	8.840
2.750	.375	2.000	DOM	9.512
2.750	.438	1.875	DOM	10.820
2.750	.500	1.750	DOM	12.015
2.750	.563	1.625	DOM	13.150
2.750	.625	1.500	DOM/CDS	14.180
2.750*	.750	1.250	CDS	16.020
2.750*	.875	1.000	CDS	17.520

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
---------------	---------------	---------------	---------------------	-------------------

2.770" O.D.

2.770	.385	2.000	DOM	9.804
-------	------	-------	-----	-------

2-7/8" O.D.

2.875	.065	2.745	CREW	1.951
2.875	.120	2.635	DOM	3.531
2.875	.156	2.563	DOM	4.528
2.875	.188	2.500	DOM	5.395
2.875	.191	2.494	DOM	5.479
2.875	.203	2.470	HREW HY	5.790
2.875	.219	2.438	DOM	6.212
2.875	.219	2.438	CDBW	6.212
2.875	.250	2.375	DOM	7.009
2.875	.313	2.250	DOM	8.564
2.875	.375	2.125	DOM	10.010
2.875	.438	2.000	DOM	11.400
2.875	.563	1.750	DOM	13.900
2.875	.625	1.625	DOM	15.020

2.918" O.D.

2.918	.211	2.496	DOM	6.100
-------	------	-------	-----	-------

* Purchased O.D. & Wall

CDS - COLD DRAWN SEAMLESS, ASTM 519
DOM - DRAWN OVER MANDREL, ASTM 513
HREW - HOT ROLLED ELECTRIC WELD, ASTM 513
CDBW - COLD DRAWN BUTT WELD, ASTM 512

CARBON MECHANICAL TUBING

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
3" O.D.				
3.000	.049	2.902	CREW	1.544
3.000	.065	2.870	DOM	2.037
3.000	.065	2.870	CREW	2.037
3.000	.065	2.870	HREW	2.037
3.000	.083	2.834	HREW	2.586
3.000	.083	2.834	DOM	2.586
3.000	.095	2.810	HREW	2.947
3.000	.095	2.810	DOM	2.947
3.000	.120	2.760	HREW	3.691
3.000	.120	2.760	DOM	3.691
3.000	.188	2.625	DOM	5.646
3.000	.219	2.562	DOM	6.505
3.000	.250	2.500	DOM	7.343
3.000	.250	2.500	CDBW	7.343
3.000	.259	2.482	DOM	7.580
3.000	.281	2.438	DOM	8.160
3.000	.313	2.374	DOM	8.982
3.000	.375	2.250	DOM	10.510
3.000	.438	2.124	DOM	11.980
3.000	.500	2.000	DOM	13.350
3.000	.500	2.000	HRS	13.350
3.000	.563	1.875	DOM	14.650
3.000	.625	1.750	DOM	15.850
3.000	.688	1.625	CDS	16.990
3.000	.750	1.500	CDS	18.020
3.000	.750	1.500	HRS	18.020
3.000*	.875	1.250	CDS	19.860
3.000	.875	1.250	HRS	19.860
3.000*	1.000	1.000	CDS	21.360
3-1/8" O.D.				
3.125	.120	2.885	DOM	3.851
3.125	.188	2.750	DOM	5.897
3.125	.250	2.625	DOM	7.676
3.125	.313	2.499	DOM	9.400
3.125	.375	2.375	DOM	11.010
3.125	.438	2.250	DOM	12.570
3.125	.500	2.125	DOM	14.020
3.125	.563	1.999	DOM	15.405
3.125	.625	1.875	DOM	16.690
3.125	.875	1.375	CDS	21.030

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
3-1/4" O.D.				
3.250	.065	3.120	DOM	2.211
3.250	.065	3.120	CREW	2.211
3.250	.095	3.060	DOM	3.201
3.250	.120	3.010	HREW	4.011
3.250	.120	3.010	DOM	4.011
3.250	.156	2.938	DOM	5.155
3.250	.188	2.874	DOM	6.148
3.250	.219	2.812	DOM	7.089
3.250	.250	2.750	DOM	8.010
3.250	.313	2.625	DOM	9.818
3.250	.344	2.562	DOM	10.676
3.250	.375	2.500	DOM	11.510
3.250	.438	2.375	DOM	13.150
3.250	.500	2.250	DOM	14.690
3.250	.563	2.124	DOM	16.160
3.250	.625	2.000	DOM	17.520
3.250	.660	1.930	CDS	18.256
3.250	.750	1.750	CDS	20.030
3.250	.750	1.750	HRS	20.030
3.250*	.875	1.500	CDS	22.190
3.250*	1.000	1.250	CDS	24.030
3.250	1.000	1.250	HRS	24.030
3-3/8" O.D.				
3.375	.120	3.135	DOM	4.172
3.375	.188	3.000	DOM	6.399
3.375	.250	2.875	DOM	8.344
3.375	.313	2.749	DOM	10.240
3.375	.375	2.625	DOM	12.020
3.375	.438	2.499	DOM	13.740
3.375	.500	2.375	DOM	15.350

*Purchased O.D. & Wall

8

CARBON MECHANICAL TUBING

CREW – COLD ROLLED ELECTRIC WELD, ASTM 513
HRS – HOT ROLLED SEAMLESS, ASTM 519
HY – HIGH YIELD WELDED

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
3.423" O.D.				
3.423	.214	2.995	DOM	7.330
3-1/2" O.D.				
3.500	.065	3.370	CREW	2.385
3.500	.065	3.370	DOM	2.385
3.500	.083	3.334	DOM	3.029
3.500	.095	3.310	DOM	3.455
3.500	.120	3.260	HREW	4.332
3.500	.120	3.260	DOM	4.332
3.500	.134	3.232	DOM	4.817
3.500	.156	3.188	DOM	5.571
3.500	.188	3.125	DOM	6.650
3.500	.216	3.068	HREW HY	7.580
3.500	.219	3.063	DOM	7.674
3.500	.250	3.000	DOM	8.678
3.500	.250	3.000	HREW	8.678
3.500	.254	2.992	DOM	8.810
3.500	.300	2.900	HREW HY	10.252
3.500	.313	2.875	DOM	10.650
3.500	.375	2.750	DOM	12.520
3.500	.438	2.625	DOM	14.320
3.500	.500	2.500	DOM	16.020
3.500	.500	2.500	HRS	16.020
3.500	.563	2.374	DOM	17.660
3.500	.625	2.250	DOM	19.190
3.500	.750	2.000	CDS	22.030
3.500	.750	2.000	HRS	22.030
3.500	.875	1.750	CDS	24.530
3.500	.875	1.750	HRS	24.530
3.500*	1.000	1.500	CDS	26.700
3.500	1.000	1.500	HRS	26.700
3.563" O.D.				
3.563	.272	3.020	DOM	9.560

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
3-5/8" O.D.				
3.625	.188	3.250	DOM	6.901
3.625	.250	3.125	DOM	9.011
3.625	.313	3.000	DOM	11.070
3.625	.375	2.875	DOM	13.020
3.625	.438	2.750	DOM	14.910
3.625	.500	2.625	DOM	16.690
3.625	.750	2.125	CDS	23.030
3-3/4" O.D.				
3.750	.065	3.620	CREW	2.560
3.750	.120	3.510	HREW	4.652
3.750	.120	3.510	DOM	4.652
3.750	.188	3.375	DOM	7.152
3.750	.250	3.250	DOM	9.345
3.750	.254	3.242	DOM	9.340
3.750	.313	3.125	DOM	11.490
3.750	.340	3.070	DOM	12.380
3.750	.344	3.062	DOM	12.513
3.750	.375	3.000	DOM	13.520
3.750	.438	2.875	DOM	15.493
3.750	.500	2.750	DOM	17.360
3.750	.500	2.750	HRS	17.360
3.750	.563	2.624	DOM	19.160
3.750	.625	2.500	DOM	20.860
3.750	.750	2.250	CDS	24.030
3.750	.750	2.250	HRS	24.030
3.750	.875	2.000	CDS	26.870
3.750	1.000	1.750	CDS	29.370
3.750	1.000	1.750	HRS	29.370

*Purchased O.D. & Wall

CDS - COLD DRAWN SEAMLESS, ASTM 519
DOM - DRAWN OVER MANDREL, ASTM 513
HREW - HOT ROLLED ELECTRIC WELD, ASTM 513
CDBW - COLD DRAWN BUTT WELD, ASTM 512

CARBON MECHANICAL TUBING

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
---------------	---------------	---------------	---------------------	-------------------

3-7/8" O.D.

3.875	.188	3.500	DOM	7.403
3.875	.250	3.375	DOM	9.679
3.875	.375	3.125	DOM	14.020
3.875	.500	2.875	DOM	18.020
3.875	.625	2.625	DOM	21.690
3.875	.750	2.375	CDS	25.030

4" O.D.

4.000	.065	3.870	DOM	2.732
4.000	.065	3.870	CREW/HREW	2.732
4.000	.083	3.834	DOM	3.472
4.000	.083	3.834	HREW	3.472
4.000	.087	3.826	HREW	3.631
4.000	.095	3.810	DOM	3.962
4.000	.120	3.760	HREW	4.973
4.000	.120	3.760	DOM	4.973
4.000	.134	3.732	DOM	5.533
4.000	.156	3.688	DOM	6.404
4.000	.188	3.624	DOM	7.654
4.000	.219	3.562	DOM	8.843
4.000	.250	3.500	DOM	10.010
4.000	.313	3.374	DOM	12.330
4.000	.375	3.250	DOM	14.520
4.000	.438	3.125	DOM	16.660
4.000	.500	3.000	DOM	18.690
4.000	.500	3.000	HRS	18.690
4.000	.563	2.875	DOM	20.670
4.000	.625	2.750	DOM	22.530
4.000	.750	2.500	CDS	26.030
4.000	.750	2.500	HRS	26.030
4.000	.875	2.250	CDS	29.200
4.000	.875	2.250	HRS	29.200
4.000	1.000	2.000	CDS	32.040
4.000	1.000	2.000	HRS	32.040
4.000	1.125	1.750	HRS	34.540
4.000*	1.250	1.500	CDS	36.713
4.000	1.250	1.500	HRS	36.713

4.005" O.D.

4.005	.500	3.005	DOM	18.720
-------	------	-------	-----	--------

4.012" O.D.

4.012	.506	3.000	CDS	18.950
-------	------	-------	-----	--------

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
---------------	---------------	---------------	---------------------	-------------------

4.095" O.D.

4.095	.180	3.735	DOM	7.526
-------	------	-------	-----	-------

4-1/8" O.D.

4.125	.250	3.625	DOM	10.350
4.125	.313	3.500	DOM	12.740
4.125	.375	3.375	DOM	15.020
4.125	.500	3.125	DOM	19.360
4.125	.625	2.875	DOM	23.360

4-1/4" O.D.

4.250	.095	4.060	DOM	4.216
4.250	.120	4.010	HREW	5.293
4.250	.120	4.010	DOM	5.293
4.250	.188	3.875	DOM	8.156
4.250	.250	3.750	DOM	10.680
4.250	.313	3.625	DOM	13.160
4.250	.375	3.500	DOM	15.520
4.250	.500	3.250	DOM	20.030
4.250	.625	3.000	DOM	24.200
4.250	.750	2.750	CDS	28.040
4.250	.750	2.750	HRS	28.040
4.250	.875	2.500	CDS	31.540
4.250	.875	2.500	HRS	31.540
4.250	1.000	2.250	CDS	34.710
4.250	1.000	2.250	HRS	34.710
4.250	1.125	2.000	CDS	37.550
4.250	1.250	1.750	HRS	40.050

*Purchased O.D. & Wall

8

CARBON MECHANICAL TUBING

CREW – COLD ROLLED ELECTRIC WELD, ASTM 513
HRS – HOT ROLLED SEAMLESS, ASTM 519
HY – HIGH YIELD WELDED

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
---------------	---------------	---------------	---------------------	-------------------

4-3/8" O.D.

4.375	.188	3.999	DOM	8.407
4.375	.284	3.807	DOM	12.408
4.375	.375	3.625	DOM	16.020
4.375	.750	2.875	CDS	29.040

4-1/2" O.D.

4.500	.065	4.370	CREW	3.079
4.500	.095	4.310	DOM	4.469
4.500	.120	4.260	HREW	5.613
4.500	.120	4.260	DOM	5.613
4.500	.188	4.124	DOM	8.658
4.500	.219	4.062	DOM	10.010
4.500	.237	4.026	HREW HY	10.790
4.500	.250	4.000	DOM	11.350
4.500	.255	3.990	DOM	11.561
4.500	.313	3.875	DOM	14.000
4.500	.375	3.750	DOM	16.520
4.500	.438	3.624	DOM	19.010
4.500	.500	3.500	DOM	21.360
4.500	.500	3.500	HRS	21.360
4.500	.625	3.250	DOM	25.870
4.500	.750	3.000	CDS	30.040
4.500	.750	3.000	HRS	30.040
4.500	.875	2.750	CDS	33.880
4.500	.875	2.750	HRS	33.880
4.500	1.000	2.500	CDS	37.380
4.500	1.000	2.500	HRS	37.380
4.500	1.125	2.250	CDS	40.550
4.500	1.125	2.250	HRS	40.550
4.500*	1.250	2.000	CDS	43.388
4.500	1.250	2.000	HRS	43.388
4.500	1.500	1.500	HRS	48.060

4.593" O.D.

4.593	.177	4.239	DOM	8.341
-------	------	-------	-----	-------

4-5/8" O.D.

4.625	.188	4.249	DOM	8.909
4.625	.313	4.000	DOM	14.410
4.625	.318	3.989	DOM	14.630
4.625	.500	3.625	DOM	22.030

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
---------------	---------------	---------------	---------------------	-------------------

4-3/4" O.D.

4.750	.120	4.510	HREW	5.934
4.750	.120	4.510	DOM	5.934
4.750	.188	4.375	DOM	9.160
4.750	.250	4.250	DOM	12.020
4.750	.313	4.125	DOM	14.830
4.750	.375	4.000	DOM	17.520
4.750	.385	3.980	DOM	17.948
4.750	.500	3.750	DOM	22.700
4.750	.500	3.750	HRS	22.700
4.750	.625	3.500	DOM	27.530
4.750	.750	3.250	CDS	32.040
4.750	.750	3.250	HRS	32.040
4.750	.875	3.000	CDS	36.210
4.750	.875	3.000	HRS	36.210
4.750	1.000	2.750	CDS	40.050
4.750	1.000	2.750	HRS	40.050
4.750	1.250	2.250	HRS	46.730
4.750	1.500	1.750	HRS	52.065

4.875" O.D.

4.875	.375	4.125	DOM	18.023
-------	------	-------	-----	--------

5" O.D.

5.000	.065	4.870	CREW	3.426
5.000	.083	4.834	HREW	4.359
5.000	.109	4.782	HREW	5.694
5.000	.120	4.760	HREW	6.254
5.000	.120	4.760	DOM	6.254
5.000	.134	4.732	HREW	6.964
5.000	.188	4.624	HREW	9.660
5.000	.188	4.624	DOM	9.660
5.000	.250	4.500	DOM	12.680
5.000	.313	4.375	DOM	15.670
5.000	.375	4.250	DOM	18.520
5.000	.438	4.125	DOM	21.340
5.000	.500	4.000	DOM	24.030
5.000	.500	4.000	HRS	24.030
5.000	.625	3.750	DOM	29.200
5.000	.625	3.750	HRS	29.200
5.000	.750	3.500	CDS	34.040
5.000	.750	3.500	HRS	34.040
5.000	.875	3.250	CDS	38.550
5.000	1.000	3.000	CDS	42.720
5.000	1.000	3.000	HRS	42.720
5.000	1.125	2.750	HRS	46.560
5.000	1.250	2.500	CDS	50.060
5.000	1.250	2.500	HRS	50.060
5.000	1.500	2.000	HRS	56.070

*Purchased O.D. & Wall

CDS - COLD DRAWN SEAMLESS, ASTM 519
DOM - DRAWN OVER MANDREL, ASTM 513
HREW - HOT ROLLED ELECTRIC WELD, ASTM 513
CDBW - COLD DRAWN BUTT WELD, ASTM 512

CARBON MECHANICAL TUBING

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
---------------	---------------	---------------	---------------------	-------------------

5-1/8" O.D.

5.125	.500	4.125	DOM	24.700
-------	------	-------	-----	--------

5-1/4" O.D.

5.250	.120	5.010	DOM	6.575
5.250	.120	5.010	HREW	6.575
5.250	.250	4.750	DOM	13.350

5.250	.313	4.624	DOM	16.500
5.250	.340	4.570	DOM	17.830
5.250	.375	4.500	DOM	19.520

5.250	.625	4.000	DOM	30.870
5.250	.750	3.750	CDS	36.050
5.250	.750	3.750	HRS	36.050

5.250	.875	3.500	HRS	40.880
5.250	1.000	3.250	CDS	45.390
5.250	1.000	3.250	HRS	45.390

5.250	1.250	2.750	HRS	53.400
5.250	1.500	2.250	HRS	60.075

5.492" O.D.

5.492	.234	5.024	DOM	13.140
-------	------	-------	-----	--------

5-1/2" O.D.

5.500	.065	5.370	HREW	3.773
5.500	.120	5.260	HREW	6.895
5.500	.120	5.260	DOM	6.895

5.500	.188	5.124	DOM	10.670
5.500	.250	5.000	DOM	14.020
5.500	.313	4.875	DOM	17.340

5.500	.375	4.750	DOM	20.530
5.500	.438	4.625	DOM	23.680
5.500	.500	4.500	DOM	26.700

5.500	.625	4.250	DOM	32.540
5.500	.750	4.000	CDS	38.050
5.500	.750	4.000	HRS	38.050

5.500	.875	3.750	CDS	43.220
5.500	.875	3.750	HRS	43.220
5.500	1.000	3.500	CDS	48.060

5.500	1.000	3.500	HRS	48.060
5.550	1.125	3.250	HRS	52.565
5.500	1.250	3.000	CDS	56.740

5.500	1.250	3.000	HRS	56.740
5.500	1.500	2.500	HRS	64.080

5-5/8" O.D.

5.625	.313	5.000	DOM	17.760
5.625	.625	4.375	DOM	33.380

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
---------------	---------------	---------------	---------------------	-------------------

5-3/4" O.D.

5.750	.250	5.250	DOM	14.690
5.750	.313	5.125	DOM	18.180
5.750	.375	5.000	DOM	21.530

5.750	.385	4.980	DOM	22.060
5.750	.500	4.750	DOM	28.040
5.750	.500	4.750	HRS	28.040

5.750	.625	4.500	DOM	34.210
5.750	.750	4.250	CDS	40.050
5.750	.750	4.250	HRS	40.050

5.750	.875	4.000	CDS	45.560
5.750	1.000	3.750	CDS	50.730
5.750	1.000	3.750	HRS	50.730

5.750	1.250	3.250	HRS	60.080
5.750	1.500	2.750	HRS	68.085

6" O.D.

6.000	.065	5.870	CREW	4.120
6.000	.065	5.870	HREW	4.120
6.000	.075	5.850	HREW	4.746

6.000	.083	5.834	HREW	5.245
6.000	.109	5.782	HREW	6.858
6.000	.120	5.760	HREW	7.536

6.000	.120	5.760	DOM	7.536
6.000	.125	5.750	DOM	7.843
6.000	.134	5.732	HREW	8.395

6.000	.180	5.640	HREW	11.188
6.000	.188	5.624	HREW	11.670
6.000	.188	5.624	DOM	11.670

6.000	.203	5.594	DOM	12.559
6.000	.250	5.500	DOM	15.350
6.000	.250	5.500	HREW	15.350

6.000	.313	5.374	DOM	19.010
6.000	.375	5.250	DOM	22.530
6.000	.500	5.000	DOM	29.370

6.000	.500	5.000	HRS	29.370
6.000	.625	4.750	DOM	35.880
6.000	.750	4.500	CDS	42.050

6.000	.750	4.500	HRS	42.050
6.000	.875	4.250	CDS	47.890
6.000	.875	4.250	HRS	47.890

6.000	1.000	4.000	CDS	53.400
6.000	1.000	4.000	HRS	53.400
6.000	1.250	3.500	CDS	63.410

6.000	1.250	3.500	HRS	63.410
6.000	1.500	3.000	HRS	72.090
6.000	1.750	2.500	HRS	79.433

6.000	2.000	2.000	HRS	85.440
-------	-------	-------	-----	--------

8

CARBON MECHANICAL TUBING

CREW – COLD ROLLED ELECTRIC WELD, ASTM 513
HRS – HOT ROLLED SEAMLESS, ASTM 519
HY – HIGH YIELD WELDED

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
6.159" O.D.				
6.159	.220	5.719	DOM	13.950
6-1/4" O.D.				
6.250	.120	6.010	DOM	7.856
6.250	.125	6.000	DOM	8.177
6.250	.250	5.750	DOM	16.020
6.250	.375	5.500	DOM	23.530
6.250	.500	5.250	DOM	30.710
6.250	.500	5.250	HRS	30.710
6.250	.625	5.000	DOM	37.550
6.250	.750	4.750	CDS	44.060
6.250	.750	4.750	HRS	44.060
6.250	.875	4.500	HRS/CDS	50.230
6.250	1.000	4.250	CDS	56.070
6.250	1.000	4.250	HRS	56.070
6.250	1.250	3.750	HRS	66.750
6.250	1.500	3.250	HRS	76.095
6-1/2" O.D.				
6.500	.188	6.124	DOM	12.670
6.500	.250	6.000	DOM	16.690
6.500	.375	5.750	DOM	24.530
6.500	.500	5.500	DOM	32.040
6.500	.625	5.250	DOM	39.220
6.500	.750	5.000	CDS	46.060
6.500	.750	5.000	HRS	46.060
6.500	.875	4.750	CDS	52.570
6.500	1.000	4.500	CDS	58.740
6.500	1.000	4.500	HRS	58.740
6.500	1.250	4.000	HRS	70.090
6.500	1.500	3.500	HRS	80.100
6.500	1.750	3.000	HRS	88.778
6.500	2.000	2.500	HRS	96.120
6-5/8" O.D.				
6.625	.120	6.385	HREW	8.337
6.625	.134	6.357	HREW	9.289
6.625	.280	6.065	HREW HY	18.970
6.625	.313	6.000	DOM	21.100
6.718" O.D.				
6.718	.250	6.218	DOM	17.270

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
6-3/4" O.D.				
6.750	.250	6.250	DOM	17.360
6.750	.375	6.000	DOM	25.530
6.750	.389	5.972	DOM	26.420
6.750	.500	5.750	DOM	33.380
6.750	.750	5.250	CDS	48.060
6.750	.750	5.250	HRS	48.060
6.750	1.000	4.750	CDS	61.410
6.750	1.000	4.750	HRS	61.410
6.750	1.250	4.250	HRS	73.430
6.750	1.500	3.750	HRS/CDS	84.105
7" O.D.				
7.000	.059	6.882	HREW	4.374
7.000	.075	6.850	HREW	5.547
7.000	.125	6.750	HREW	9.178
7.000	.134	6.732	HREW	9.826
7.000	.188	6.624	HREW	13.680
7.000	.188	6.624	DOM	13.680
7.000	.250	6.500	DOM	18.020
7.000	.375	6.250	DOM	26.530
7.000	.500	6.000	HRS	34.710
7.000	.500	6.000	DOM	34.710
7.000	.507	5.986	DOM	35.158
7.000	.625	5.750	DOM	42.550
7.000	.750	5.500	CDS	50.060
7.000	.750	5.500	HRS	50.060
7.000	1.000	5.000	CDS	64.080
7.000	1.000	5.000	HRS	64.080
7.000	1.250	4.500	HRS/CDS	76.760
7.000	1.500	4.000	HRS	88.110
7.000	1.750	3.500	HRS	98.123
7.000	2.000	3.000	HRS	106.800
7-1/4" O.D.				
7.250	.250	6.750	DOM	18.690
7.250	.375	6.500	DOM	27.530
7.250	.500	6.250	DOM	36.050
7.250	.625	6.000	DOM	44.220
7.250	.645	5.960	CDS	45.500
7.250	.750	5.750	CDS	52.070
7.250	.750	5.750	HRS	52.070
7.250	1.000	5.250	CDS	66.750
7.250	1.000	5.250	HRS	66.750
7.250	1.250	4.750	HRS	80.100
7.250	1.500	4.250	HRS	92.115

HRS – HOT ROLLED SEAMLESS, ASTM 519
CDS – COLD DRAWN SEAMLESS, ASTM 519
DOM - DRAWN OVER MANDREL, ASTM 513
HREW - HOT ROLLED ELECTRIC WELD, ASTM 513

CARBON MECHANICAL TUBING

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
7-1/2" O.D.				
7.500	.250	7.000	DOM	19.360
7.500	.375	6.750	DOM	28.540
7.500	.500	6.500	DOM	37.380
7.500	.625	6.250	DOM	45.890
7.500	.750	6.000	CDS	54.070
7.500	.750	6.000	HRS	54.070
7.500	1.000	5.500	CDS	69.420
7.500	1.000	5.500	HRS	69.420
7.500	1.250	5.000	HRS	83.440
7.500	1.500	4.500	HRS	96.120
7.500	1.750	4.000	HRS	107.468
7.500	2.000	3.500	HRS	117.480
7.500	2.500	2.500	HRS	133.500
7-5/8" O.D.				
7.625	.500	6.625	HRS-A-106	38.080
7.625	.875	5.875	HRS-A-106	63.140
7.625	1.000	5.625	HRS-A-519	70.760
7-3/4" O.D.				
7.750	.250	7.250	DOM	20.030
7.750	.375	7.000	DOM	29.540
7.750	.500	6.750	DOM	38.720
7.750	.625	6.500	DOM	47.560
7.750	.641	6.468	DOM	38.850
7.750	.750	6.250	CDS	56.070
7.750	.750	6.250	HRS	56.070
7.750	1.000	5.750	CDS	72.090
7.750	1.000	5.750	HRS	72.090
7.750	1.250	5.250	HRS	86.780
7.750	1.500	4.750	HRS	100.100
8" O.D.				
8.000	.059	7.882	HREW	5.004
8.000	.075	7.850	HREW	6.348
8.000	.083	7.834	HREW	7.018
8.000	.109	7.782	HREW	9.186
8.000	.120	7.760	HREW	10.100
8.000	.125	7.750	HREW	10.510
8.000	.134	7.732	HREW	11.260
8.000	.188	7.624	HREW	15.690
8.000	.250	7.500	DOM	20.690
8.000	.250	7.500	HREW	20.690
8.000	.375	7.250	DOM	30.540
8.000	.500	7.000	DOM	40.050
8.000	.500	7.000	HRS	40.050
8.000	.625	6.750	DOM	49.230
8.000	.750	6.500	CDS	58.070
8.000	.750	6.500	HRS	58.070
8.000	1.000	6.000	CDS	74.760
8.000	1.000	6.000	HRS	74.760
8.000	1.250	5.500	HRS	90.110

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
8" O.D. (continued)				
8.000	1.500	5.000	HRS	104.100
8.000	1.750	4.500	HRS	116.813
8.000	2.000	4.000	HRS	128.160
8.000	2.250	3.500	HRS	138.173
8.000	2.500	3.000	HRS	146.850
8-1/4" O.D.				
8.250	.375	7.500	DOM	31.540
8.250	.500	7.250	DOM	41.390
8.250	.750	6.750	CDS	60.080
8.250	.750	6.750	HRS	60.080
8.250	1.000	6.250	HRS	77.430
8.250	1.250	5.750	HRS	93.450
8.250	1.500	5.250	HRS	108.100
8-1/2" O.D.				
8.500	.250	8.000	DOM	22.030
8.500	.375	7.750	DOM	32.540
8.500	.500	7.500	DOM	42.720
8.500	.500	7.500	HRS	42.720
8.500	.750	7.000	CDS	62.080
8.500	.750	7.000	HRS	62.080
8.500	.779	6.942	CDS	64.240
8.500	1.000	6.500	CDS	80.100
8.500	1.000	6.500	HRS	80.100
8.500	1.250	6.000	HRS	96.790
8.500	1.500	5.500	HRS	112.100
8.500	1.750	5.000	HRS	126.158
8.500	2.000	4.500	HRS	138.840
8.500	2.500	3.500	HRS	160.200
8-5/8" O.D.				
8.625	.109	8.407	HREW	9.914
8.625	.134	8.357	HREW	12.150
8.625	.500	7.625	HRS-A-106	43.430
8.625	.594	7.437	HRS-A-106	51.000
8.625	.719	7.187	HRS-A-106	60.770
8.625	.812	7.001	HRS-A-106	67.820
8.625	.875	6.875	HRS-A-106	72.490
8.625	.906	6.813	HRS-A-106	74.760
8-3/4" O.D.				
8.750	.375	8.000	DOM	33.540
8.750	.500	7.750	HRS	44.060
8.750	.750	7.250	HRS	64.080
8.750	1.000	6.750	CDS	82.770
8.750	1.000	6.750	HRS	82.770
8.750	1.250	6.250	HRS	100.100
8.750	1.500	5.750	HRS	116.100
8.750	2.000	4.750	HRS	144.180

8

CARBON MECHANICAL TUBING

DOM – DRAWN OVER MANDREL, ASTM 513
HREW – HOT ROLLED ELECTRIC WELD, ASTM 513

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
9" O.D.				
9.000	.250	8.500	DOM	23.360
9.000	.500	8.000	DOM	45.390
9.000	.750	7.500	CDS	66.080
9.000	.750	7.500	HRS	66.080
9.000	.779	7.442	CDS	68.400
9.000	1.000	7.000	CDS	85.440
9.000	1.000	7.000	HRS	85.440
9.000	1.250	6.500	HRS	103.500
9.000	1.500	6.000	HRS	120.200
9.000	1.750	5.500	HRS	135.503
9.000	2.000	5.000	HRS	149.520
9.000	2.250	4.500	HRS	162.203
9.000	2.500	4.000	HRS	173.550
9.000	3.000	3.000	HRS	192.240
9-1/4" O.D.				
9.250	.250	8.750	DOM	24.030
9.250	.375	8.500	DOM	35.540
9.250	.500	8.250	DOM	46.730
9.250	.750	7.750	HRS	68.090
9.250	1.000	7.250	HRS	88.110
9.250	1.250	6.750	HRS	106.800
9.250	1.500	6.250	HRS	124.200
9.270" O.D.				
9.270	.662	7.946	DOM	60.860
9-1/2" O.D.				
9.500	.250	9.000	DOM	24.700
9.500	.339	8.822	DOM	33.188
9.500	.375	8.750	DOM	36.550
9.500	.500	8.500	DOM	48.060
9.500	.500	8.500	HRS	48.060
9.500	.625	8.250	DOM	59.240
9.500	.750	8.000	CDS	70.090
9.500	.750	8.000	HRS	70.090
9.500	.767	7.966	CDS	71.537
9.500	.904	7.692	CDS	83.000
9.500	1.000	7.500	HRS	90.780
9.500	1.250	7.000	HRS	110.100
9.500	1.500	6.500	HRS	128.200
9.500	1.750	6.000	HRS	144.848
9.500	2.000	5.500	HRS	160.200
9-5/8" O.D.				
9.625	.500	8.625	HRS-A-106	48.770
9-3/4" O.D.				
9.750	.250	9.250	DOM	25.365
9.750	.500	8.750	DOM	49.400
9.750	.750	8.250	HRS	72.090
9.750	1.000	7.750	HRS	93.450
9.750	1.500	6.750	HRS	132.200

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
10" O.D.				
10.000	.075	9.850	HREW	7.950
10.000	.109	9.782	HREW	11.510
10.000	.125	9.750	HREW	13.180
10.000	.134	9.732	HREW	14.120
10.000	.188	9.624	HREW	19.700
10.000	.250	9.500	DOM	26.033
10.000	.250	9.500	HREW	26.030
10.000	.375	9.250	DOM	38.550
10.000	.500	9.000	DOM	50.730
10.000	.500	9.000	HRS	50.730
10.000	.750	8.500	CDS	74.090
10.000	.750	8.500	HRS	74.090
10.000	1.000	8.000	CDS	96.120
10.000	1.000	8.000	HRS	96.120
10.000	1.250	7.500	HRS	116.800
10.000	1.500	7.000	HRS	136.200
10.000	1.750	6.500	HRS	154.193
10.000	2.000	6.000	HRS	170.880
10.000	2.250	5.500	HRS	186.233
10.000	2.500	5.000	HRS	200.250
10.000	3.000	4.000	HRS	224.280
10-1/4" O.D.				
10.250	.500	9.250	DOM	52.070
10.250	.750	8.750	HRS	76.100
10.250	1.000	8.250	HRS	98.790
10.250	1.250	7.750	HRS	120.200
10.250	1.500	7.250	HRS	140.200
10-1/2" O.D.				
10.500	.250	10.000	DOM	27.370
10.500	.500	9.500	DOM	53.400
10.500	.750	9.000	CDS	78.100
10.500	.750	9.000	HRS	78.100
10.500	1.000	8.500	CDS	101.500
10.500	1.000	8.500	HRS	101.500
10.500	1.250	8.000	HRS	123.500
10.500	1.500	7.500	HRS	144.200
10.500	1.750	7.000	HRS	163.538
10.500	2.000	6.500	HRS	181.560
10.500	2.500	5.500	HRS	213.600

HRS – HOT ROLLED SEAMLESS, ASTM 519
CDS – COLD DRAWN SEAMLESS, ASTM 519

CARBON MECHANICAL
TUBING

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
10-3/4" O.D.				
10.750	.134	10.482	HREW	15.190
10.750	.250	10.250	DOM	28.040
10.750	.375	10.000	DOM	41.550
10.750	.500	9.750	DOM	54.740
10.750	.594	9.562	HRS	64.490
10.750	.719	9.312	HRS	77.100
10.750	.750	9.250	HRS	80.100
10.750	.844	9.062	HRS	89.380
10.750	1.000	8.750	HRS	104.100
10.750	1.250	8.250	HRS	126.830
10.750	1.500	7.750	HRS	148.200
10.750	1.750	7.250	HRS	168.210
11" O.D.				
11.000	.250	10.500	DOM	28.700
11.000	.500	10.000	DOM	56.070
11.000	.500	10.000	HRS	56.070
11.000	.750	9.500	HRS	82.103
11.000	.875	9.250	HRS	94.618
11.000	1.000	9.000	HRS	106.800
11.000	1.250	8.500	HRS	130.163
11.000	1.500	8.000	HRS	152.190
11.000	1.750	7.500	HRS	172.883
11.000	2.000	7.000	HRS	192.240
11.000	2.500	6.000	HRS	226.950
11.000	3.000	5.000	HRS	256.320
11-1/4" O.D.				
11.250	.750	9.750	HRS	84.105
11.250	1.000	9.250	HRS	109.470
11.250	1.500	8.250	HRS	156.195
11-1/2" O.D.				
11.500	.500	10.500	HRS	58.740
11.500	.750	10.000	HRS	86.108
11.500	1.000	9.500	HRS	112.140
11.500	1.250	9.000	HRS	136.838
11.500	1.500	8.500	HRS	160.200
11.500	1.750	8.000	HRS	182.228
11.500	2.000	7.500	HRS	202.920
11.500	2.500	6.500	HRS	240.300
11-3/4" O.D.				
11.750	.750	10.250	HRS	88.110
11.750	1.000	9.750	HRS	114.810
11.750	1.250	9.250	HRS	140.210
11.750	1.750	8.250	HRS	186.900

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
12" O.D.				
12.000	.109	11.782	HREW	13.840
12.000	.134	11.732	HREW	16.980
12.000	.188	11.624	HREW	23.720
12.000	.250	11.500	DOM	31.373
12.000	.250	11.500	HREW	31.370
12.000	.375	11.250	DOM	46.558
12.000	.500	11.000	DOM	61.410
12.000	.500	11.000	HRS	61.410
12.000	.750	10.500	CDS	90.113
12.000	.750	10.500	HRS	90.113
12.000	1.000	10.000	CDS	117.480
12.000	1.000	10.000	HRS	117.480
12.000	1.040	9.917	CDS	128.470
12.000	1.250	9.500	HRS	143.513
12.000	1.500	9.000	HRS	168.210
12.000	1.750	8.500	HRS	191.573
12.000	2.000	8.000	HRS	213.600
12.000	2.250	7.500	HRS	234.293
12.000	2.500	7.000	HRS	253.650
12.000	3.000	6.000	HRS	288.360
12-1/8" O.D.				
12.125	.375	11.375	DOM	47.059
12-1/4" O.D.				
12.250	.750	10.750	HRS	92.115
12.250	1.000	10.250	HRS	120.150
12.250	1.250	9.750	HRS	146.850
12.250	1.500	9.250	HRS	172.215
12-1/2" O.D.				
12.500	.750	11.000	HRS	94.118
12.500	1.000	10.500	HRS	122.820
12.500	1.250	10.000	HRS	150.188
12.500	1.500	9.500	HRS	176.220
12.500	1.750	9.000	HRS	200.918
12.500	2.000	8.500	HRS	224.280
12.500	2.500	7.500	HRS	267.000

8

CARBON MECHANICAL TUBING

HREW – HOT ROLLED ELECTRIC WELD, ASTM 513

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
12-3/4" O.D.				
12.750	.500	11.750	HRS	65.420
12.750	.562	11.626	HRS	73.220
12.750	.688	11.374	HRS	88.710
12.750	.844	11.062	HRS	107.420
12.750	1.000	10.750	HRS	125.610
12.750	1.125	10.500	HRS	139.670
12.750	1.312	10.126	HRS	160.420
12.750	1.750	9.250	HRS	205.590
13" O.D.				
13.000	.500	12.000	HRS-A-106	66.750
13.000	.750	11.500	HRS-A-106	98.123
13.000	1.000	11.000	HRS-A-106	128.160
13.000	1.250	10.500	HRS-A-106	156.863
13.000	1.500	10.000	HRS-A-106	184.230
13.000	1.750	9.500	HRS-A-106	210.263
13.000	2.000	9.000	HRS-A-106	234.960
13.000	2.500	8.000	HRS-A-106	280.350
13.000	3.000	7.000	HRS-A-106	320.400
13-3/8" O.D.				
13.375	.750	11.875	HRS-A-106	101.126
13.375	1.000	11.375	HRS-A-106	132.165
13.375	1.250	10.875	HRS-A-106	161.869
13.375	1.500	10.375	HRS-A-106	190.238
13.375	2.000	9.375	HRS-A-106	242.970
14" O.D.				
14.000	.109	13.782	HREW	16.170
14.000	.134	13.732	HREW	19.840
14.000	.188	13.624	HREW	27.730
14.000	.500	13.000	HRS	72.160
14.000	.594	12.812	HRS	85.130
14.000	.750	12.500	HRS	106.230
14.000	.938	12.124	HRS	130.980
14.000	1.094	11.812	HRS	150.930
14.000	1.250	11.500	HRS	170.370
14.000	1.406	11.188	HRS	189.290
14.000	1.500	11.000	HRS	200.250
14.000	1.750	10.500	HRS	228.950
14.000	2.000	10.000	HRS	256.320
14.000	2.250	9.500	HRS	282.350
14.000	2.500	9.000	HRS	307.050
14.000	3.000	8.000	HRS	352.440
14.000	4.000	6.000	HRS-A-106	427.200
14-3/8" O.D.				
14.375	1.000	12.375	HRS-A-106	142.845
14.375	1.250	11.875	HRS-A-106	175.219
14.375	1.500	11.375	HRS-A-106	206.258
14.375	2.000	10.375	HRS-A-106	264.330
14.375	2.500	9.375	HRS-A-106	317.063

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/ Grade	Wt./Ft. (lbs.)
15" O.D.				
15.000	.375	14.250	HRS-A-106	58.573
15.000	.500	14.000	HRS-A-106	77.430
15.000	.750	13.500	HRS-A-106	114.143
15.000	1.000	13.000	HRS-A-106	149.520
15.000	1.250	12.500	HRS-A-106	183.563
15.000	1.500	12.000	HRS-A-106	216.270
15.000	1.750	11.500	HRS-A-106	247.643
15.000	2.000	11.000	HRS-A-106	277.680
15.000	2.250	10.500	HRS-A-106	300.375
15.000	2.250	10.500	HRS-A-106	306.383
15.000	2.500	10.000	HRS-A-106	333.750
15.000	3.000	9.000	HRS-A-106	384.480
15-1/2" O.D.				
15.500	.750	14.000	HRS-A-106	118.148
15.500	1.000	13.500	HRS-A-106	154.860
15.500	1.250	13.000	HRS-A-106	190.238
15.500	1.500	12.500	HRS-A-106	224.280
15.500	1.750	12.000	HRS-A-106	256.988
15.500	2.000	11.500	HRS-A-106	288.360
15.500	2.500	10.500	HRS-A-106	347.100
16" O.D.				
16.000	.109	15.782	HREW	18.500
16.000	.134	15.732	HREW	22.730
16.000	.500	15.000	HRS	82.850
16.000	.656	14.688	HRS	107.600
16.000	.844	14.312	HRS	136.740
16.000	1.031	13.938	HRS	164.980
16.000	1.219	13.562	HRS	192.610
16.000	1.438	13.124	HRS	223.850
16.000	1.500	13.000	HRS-A-106	232.290
16.000	1.594	12.812	HRS	245.480
16.000	1.750	12.500	HRS	266.330
16.000	2.000	12.000	HRS	299.040
16.000	2.250	11.500	HRS	330.413
16.000	2.500	11.000	HRS	360.450
16.000	3.000	10.000	HRS	416.520
16-1/2" O.D.				
16.500	.750	15.000	HRS-A-106	126.158
16.500	1.000	14.500	HRS-A-106	165.540
16.500	1.250	14.000	HRS-A-106	203.588
16.500	1.500	13.500	HRS-A-106	240.300
16.500	2.000	12.500	HRS-A-106	309.720

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/Grade	Wt./Ft. (lbs.)
17" O.D.				
17.000	.500	16.000	HRS-A-106	88.110
17.000	.750	15.500	HRS-A-106	130.163
17.000	1.000	15.000	HRS-A-106	170.880
17.000	1.250	14.500	HRS-A-106	210.263
17.000	1.500	14.000	HRS-A-106	248.310
17.000	2.000	13.000	HRS-A-106	320.400
17.000	2.500	12.000	HRS-A-106	387.150
17.000	2.875	11.250	HRS-A-106	433.708
17.000	3.000	11.000	HRS-A-106	448.560
17-1/2" O.D.				
17.500	1.000	15.500	HRS-A-106	176.220
17.500	1.250	15.000	HRS-A-106	216.938
17.500	1.500	14.500	HRS-A-106	256.320
17.500	2.000	13.500	HRS-A-106	331.080
18" O.D.				
18.000	.500	17.000	HRS	93.540
18.000	.562	16.876	HRS	104.760
18.000	.625	16.750	HRS	116.080
18.000	.750	16.500	HRS	138.300
18.000	.938	16.124	HRS	171.080
18.000	1.156	15.688	HRS	208.150
18.000	1.375	15.250	HRS	244.370
18.000	1.562	14.876	HRS-A-106	274.200
18.000	1.781	14.438	HRS-A-106	308.500
18.000	2.000	14.000	HRS-A-106	341.760
18.000	2.500	13.000	HRS-A-106	413.850
18.000	3.000	12.000	HRS-A-106	480.600
18-1/2" O.D.				
18.500	1.000	16.500	HRS-A-106	186.900
18.500	1.250	16.000	HRS-A-106	230.288
18.500	1.500	15.500	HRS-A-106	272.340
18.500	2.000	14.500	HRS-A-106	352.440
19" O.D.				
19.000	.109	18.782	HREW	21.990
19.000	.750	17.500	HRS-A-106	146.183
19.000	1.000	17.000	HRS-A-106	192.240
19.000	1.250	16.500	HRS-A-106	236.963
19.000	1.500	16.000	HRS-A-106	280.350
19.000	1.750	15.500	HRS-A-106	322.403
19.000	2.000	15.000	HRS-A-106	363.120
19.000	2.500	14.000	HRS-A-106	440.550
19.000	3.000	13.000	HRS-A-106	512.640

O.D. (In.)	Wall (In.)	I.D. (In.)	Condition/Grade	Wt./Ft. (lbs.)
20" O.D.				
20.000	.500	19.000	HRS	104.230
20.000	.594	18.812	HRS	123.230
20.000	.625	18.750	HRS	129.450
20.000	.750	18.500	HRS	154.330
20.000	.812	18.376	HRS	166.560
20.000	1.031	17.938	HRS	209.060
20.000	1.281	17.438	HRS	256.340
20.000	1.500	17.000	HRS-A-106	296.400
20.000	1.750	16.500	HRS-A-106	341.100
20.000	1.968	16.064	HRS-A-106	379.000
20.000	2.500	15.000	HRS-A-106	467.250
20.000	3.000	14.000	HRS-A-106	544.680
21" O.D.				
21.000	.750	19.500	HRS-A-106	162.203
21.000	1.000	19.000	HRS-A-106	213.600
21.000	1.500	18.000	HRS-A-106	312.390
21.000	1.750	17.500	HRS-A-106	359.783
21.000	2.000	17.000	HRS-A-106	405.840
21.000	2.500	16.000	HRS-A-106	493.950
21.000	3.000	15.000	HRS-A-106	576.720
22" O.D.				
22.000	.500	21.000	HRS	114.920
22.000	.750	20.500	HRS	170.370
22.000	.875	20.250	HRS	197.600
22.000	1.000	20.000	HRS	224.280
22.000	1.125	19.750	HRS	251.050
22.000	1.500	19.000	HRS-A-106	328.410
22.000	2.000	18.000	HRS-A-106	427.200
22.000	2.500	17.000	HRS-A-106	520.650
22.000	3.000	16.000	HRS-A-106	608.760
23" O.D.				
23.000	1.000	21.000	HRS-A-106	234.960
23.000	1.500	20.000	HRS-A-106	344.430
23.000	2.000	19.000	HRS-A-106	448.560
23.000	3.000	17.000	HRS-A-106	640.800
24" O.D.				
24.000	.500	23.000	HRS	125.610
24.000	.688	22.624	HRS	171.450
24.000	.750	22.500	HRS	186.200
24.000	.969	22.064	HRS	238.570
24.000	1.219	21.562	HRS-A-106	296.580
24.000	1.531	20.938	HRS-A-106	367.400
24.000	1.812	20.376	HRS-A-106	429.400
24.000	2.062	19.876	HRS-A-106	483.100
24.000	2.343	19.314	HRS-A-106	541.900
24.000	2.500	19.000	HRS-A-106	574.050
24.000	3.000	18.000	HRS-A-106	672.840
26" O.D.				
26.000	1.000	24.000	HRS-A-106	267.000
26.000	1.500	23.000	HRS-A-106	392.490
26.000	2.000	22.000	HRS-A-106	512.640
26.000	3.000	20.000	HRS-A-106	736.920

